# Efficient large area cleaning

- at lower total cost





### The CS7010 Hybrid and ePower combination sv

Suitable for warehouses, manufacturing plants, stadium, university, parking ramps and lots

- 1 ClearView sightlines and automatic speed reduction in turns for safer operation
- 2 High impact-absorbing polymer body panels won't dent, corrode or damage facility
- **3** Hybrid Drive backup battery power adds user convenience to drive to refueling station
- **4** High-capacity 198 liter front dry sweeper debris hopper with high-lift system
- 5 High performance Donaldson PowerCore<sup>®</sup> nanofiber filter with variablefrequency shaker
- 6 Heavy-gauge industrial steel unibody frame
- 7 Available with patented DustGuard<sup>™</sup> airborne dust suppression technology
- 8 Standard dual side brooms sweep entire squeegee path to minimize fouling
- **9** Seat-accessible hopper safety prop rod



### veeper-scrubbers



- 10 Optional dual-tank EcoFlex<sup>™</sup> System provides the most flexible cleaning solution for industrial applications
- Tools-free tilt-out/lift-off recovery tank
- *High-capacity 285 liter corrosionproof solution and recovery tanks*
- Powerful dual vacuum motors deliver high waterlift and airflow to ensure a safe, dry floor
- SmartFlow technology decreases water and chemical usage
- Patented breakaway squeegee mechanism with tools-free servicing
- Disc scrub deck with integrated, powerful edge cleaning capability
- Brushes, brooms and squeegee can be replaced without tools
- Electronically-controlled electric drives are IP55 rated for easy cleaning and reliable operation

## More effective cleaning

#### DustGuard™



Patented DustGuard<sup>™</sup> is proven to reduce airborne dust generated by side broom sweeping. An ultra fine fog suppresses fugitive dust

#### HYBRID Technology



The CS7010 delivers unparalleled performance, while replacing power-hungry, high-maintenance hydraulic systems with efficient, state-of-the-art Electric Drive technology

#### EcoFlex<sup>™</sup> System



EcoFlex<sup>™</sup> System with interchangeable dual detergent cartridges are refillable with your favorite brand of detergents

### UltraWeb<sup>®</sup> Nanofilter



High-capacity Donaldson PowerCore® UltraWeb® nanofilter synthetic media filter with MERV 13 rating with a variable-frequency shaker. Provides superior dust/ dirt holding capacity in a more compact package for longer filter life and improved dust control compared to conventional pleated filters

#### Intuitive Control Panel



Intuitive controls with OneTouch<sup>™</sup> operation reduce training time, improve productivity and deliver more consistent cleaning results

#### SmartFlow™



SmartFlow<sup>™</sup> adjusts solution flow with the machine's speed, using water and chemicals. Proportionally higher productivity with fewer dump and refill cycles per tankful

# Simpler cleaning

### Pivoting Scrub Deck



Retractable 10 cm offset disc deck enhances edge scrubbing and resists damage from accidental impact



We designed the CS7010 to provide quick access to all vital systems for easier inspection and maintenance

# Safer cleaning

#### Speed reduction



Automatic speed reduction in turns for improved safety and reduced risk of impact damage

#### Ergonomic operator compartment



The CS7010 has a fully adjustable seat and tilt steering



#### Kubota<sup>®</sup> Industrial Engine

- Rugged industrial engine design offering superior operating life
- Best in industry quiet operation
- Gear-driven valve train eliminates timing belts or chains, improving reliability and reducing maintenance costs

#### **Technical specifications**

Models		CS7010 Battery	CS7010 LPG/Gas Hybrid	CS7010 Diesel Hybrid
Configuration		Independent front dry sweeping w/dust control and rear scrubbing functions Electronically controlled electric drives for all sweeping and scrubbing functions Electrically driven hydraulic power unit for hopper raise/lower functions		
Sweeping System				
Sweeping Path w/Dual Side Brooms		154 cm - Squeegee path width is fully swept		
Main Broom		90 cm x 31 cm		
Sweeping Coverage Rate Per Hour		13,600 m <sup>2</sup>		
Dust Control System		10,7 m <sup>2</sup> Donaldson high-capacity PowerCore <sup>®</sup> UltraWeb <sup>®</sup> filter w/synthetic media. Variable frequency automatic filter shaker		
Hopper Dump Height (Max.)		152 cm		
Hopper Capacity		198 liter 136 kg		
DustGuard <sup>™</sup> Tank Capacity <sup>1</sup>		110 liter		
Scrubbing and Recovery	v Systems			
Scrubbing Path and Brushes		165 cm - 3 x 43 cm disc		
Scrubbing Coverage Rate Per Hour		11,000 m <sup>2</sup>		
Scrub Pressure		Three scrub pressure settings up to 182 kg of down force at maximum setting		
Recovery/Solution Tank Capacity		285 liter each		
Recovery Vacuum		Dual vac fan motors capable of 165 cm waterlift		
Power and Propulsion S	ystems			
Power System		Battery: 36 V/770 Ah	Kubota WG972: 3 cyl., 0,96 liter 30 hp (22.0 kW)	Kubota D1305 <sup>3</sup> : 3 cyl., 1,26 liter 29 hp (21.7 kW)
Propulsion System		Variable speed brushless A/C drive		
Propel Speed (Variable) Transport Sweeping/Scrubbing		8,9 km/h 5,6 km/h w/override capability		
Operational Run Time	Sweeping/Scrubbing <sup>2</sup>	5.4 hrs. w/770 Ah battery	LPG - 5.5 hrs. w/14.5 kg tank Gas - 5.9 hrs. w/35 liter tank	15 hrs. w/35 liter tank
Gradeability Transport @ Gross Weight Scrubbing/Sweeping		21% (12 deg.) 17.6% (10 deg.)		
Dimensions/Weight/Sou	Ind/Environmental			
Length		262 cm		
Width		165 cm		
Height		[150 cm] [208 cm std. overhead guard] [201 cm low clearance overhead guard]		
Minimum Aisle Turn		264 cm		
Weight : GVW		2,593 kg	2,121 kg	2,058 kg
Empty		2,124 kg	1,649 kg	1,593 kg
Sound Level (IEC60335-2-72)		72 dB(A)	82 dB(A)	81 dB(A)
Water Ingression		All electric d	rive motors and actuators rated IP55 for w	vater washdown

Specifications are subject to change without notice.

<sup>1</sup> DustGuard<sup>™</sup> optional
<sup>2</sup> Measured run time using low scrubbing and sweeping mode at normal operating speeds on smooth floors (actual results will be application dependent)
<sup>3</sup> Meets EPA emission standards under 40 CFR 1039.625

CS7010 models shown in photos may feature optional accessories

