Better ergonomics, better reliability, and better cleaning









An integrated on-board charger enables easy plug-in and battery charge at any outlet



Built-in squeegee hanging system on recovery tank for easy machine transfer in narrow areas



A debris tray captures the dirt from the suction hose to prevent it from entering the recovery tank

A thoroughly modern machine for efficient cleaning

User friendly, easy to operate and highly productive

Welcome to the modern world of cleaning: a world in which efficiency is essential, where ergonomic and environmental considerations are vital, and where the ability to meet the most demanding customer expectations is paramount.

Nilfisk's generation of ride-on scrubber dryers feature all that modern cleaning professionals demand, and more. Better reliability, outstanding traction, a decibel level low enough to make daytime cleaning possible in even the most sensitive areas, and amazing efficiency in both scrubbing and drying performance.

Added to which there are innovations such as the ecoflex[™] concept, for easily adjust of amount of water, precise detergent metering and pressure to the surface. The BR 755/755C/855 series is simply the better choice.

- Flexible software menu gives a tailored machine to suit the specific application
- Waterproof one touch control panel simplifies operations for better results
- · High manoeuvrability allows cleaning in congested areas
- · Adjustable scrubbing pressure ensures better results regardless of the dirt level
- Integrated 3 stage vacuum reduces noise levels to just 63 dB(A)
- New squeegee concept: compact, easy to adjust and more reactive
- · Patented design for a top drying efficiency
- Large battery compartment enables a 360Ah battery tray for more than 4.5 hours running time
- Robust design ideal for commercial and industrial cleaning such as supermarkets, shopping malls, schools, airports, hospitals, warehouses, food and iron&metal industry



Easy change of cartridge, now located underneath the seat



Both the cleaning deck and the squeegee sides are well protected by large roller bumpers



Reliability is also our mantra when it comes to service

A Nilfisk machine functions optimally when cared for by regular service and maintenance visits. Therefore we have created the optimal service solution: three levels of service reflecting different requirements and an optional supply of a substitute machine in critical situations.

Service Solutions Standard – Professional maintenance

Your contract encompasses two yearly maintenance visits and 48 hours response time. Breakdown visits and spare parts are billed separately.

Service Solutions Plus – Optimised performance

With the Plus solution you have a firm grip on your maintenance and repair costs while knowing that your performance is never compromised, only optimised.

Service Solutions Premium – Maximised uptime

If uptime is your absolute top priority and key concern, Service Solutions Premium is the best choice. A quarterly maintenance visit is included, and there are no sudden financial surprises.

- Large opening to the recovery tank allows easy cleaning
- Solution and recovery tanks are made of crack-, dent- and chemical-resistant tough polyethylene
- Emptying of the solution tank is fast and easy with the Easy-FlowTM drain hose system
 - Unique squeegee design for excellent drying performance



Front and rear polyurethane wheels for outstanding traction and high durability

- Spacious driving seat and position allows excellent field of vision with ClearView[™] sight lines
- Detergent and water are mixed in the exact proportion needed to ensure optimal cleaning results

The side bumper protects the deck and squeegee

 The side skirts adjust to prevent splash and to guide the solution to the squeegee for faster drying

Technical specifications

Description	Unit	BR 755	BR 755C	BR 855
Voltage	V	24	24	24
Rated power	W	2040	1920	2160
Sound pressure level at 1.5m	dB(A)	63.7	63.7	63.7
Productivity rate theoretical/ actual	m²/h	4500/3150	5400/3800	4500/3150
Scrubbing width	mm	710	710	860
Max speed	km/h	6.3	6.3	6.3
Solution/recovery tank	litre	106/106	106/106	106/106
Brush/pad diameter	mm	2x355	cyl.	2x430
Brush pressure	kg	40/65/96	27/36/45	40/65/96
Brush speed	rpm	250	900	250
Battery compartment size (lxwxh)	mm	667x406x533	667x406x533	6667x406x533
Length x width x height (w/o squeegee)	cm	152x77x131	152x80x131	152x92x131
Weight	kg	244	248	246
Operating weight	kg	658	662	660

Specifications and details are subject to change without prior notice.

Nilfisk A/S

Kornmarksvej 1 · DK-2605 Brøndby · Denmark Tel.: +45 43 23 81 00 · Fax: +45 43 43 77 00 mail.com@nilfisk.com www.nilfisk.com

