T7 Micro-Rider Floor Scrubber

Easy Operation & Maintenance

Clean both large areas and tight spaces easily with a floor scrubber designed for greater efficiency and less environmental impact.

Available Technologies



ec-H2O NanoClean®



IRIS[®] Asset Manager





Easily train new operators to use the simple, intuitive controls.



Leave behind no cleaning solution even around 180-degree turns, with the T7's equal-pressure, parabolic squeegee.



"No hassle" squeegee system, there are no tools for maintenance and the blade is factory set at the optimum recovery angle.



More T7 Features

- 1. Exclusive Hygenic[®] solution and recovery tanks are fully accessible for easy cleaning.
- 2. Decrease the chance of accidents with automatic braking and parking brake actuation.
- **3. Quickly** remove and replace brushes and squeegees.



T7 Specifications

| FEATURE | SPECIFICATION | |
|---|--|--|
| | 26 in/660 mm | 32 in/810 mm |
| Productivity (per hour) Theoretical Max | 45,760 ft² / 4,250 m² | 56,320 ft² / 5,230 m² |
| Estimated Coverage* Conventional | 23,760 ft² / 2,210 m² | 29,700 ft² / 2,760 m² |
| Estimated Coverage*ec-H2O NanoClean® | 31,680 ft² / 2,950 m² | 39,600 ft² / 3,680 m² |
| Brush motor | .6 hp / 0.45 kW | |
| Brush/pad RPM | 225 rpm | |
| Brush/pad pressure | 80, 120, 160 lb / 36, 54, 73 kg | |
| Solution tank capacity | 29 gal / 110 L | |
| Recovery tank capacity | 29 gal / 110 L | |
| Vacuum motor | 0.6 hp / 0.45 kW | |
| Vacuum waterlift | 70 in / 1,780 mm | |
| System voltage | 24 volt | |
| Battery run time (up to hours)** | 3.0 | |
| Length x width x height | 60 x 33.25 x 50 in 1,520 x 850 x 1,270 mm | 60 x 39.25 x 50 in 1,520 x 1,000 x 1,270 mm |
| Weight (with Batteries) | 850 lb / 386 kg | |
| Sound level (operator's ear)*** | 67 dBA | |

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.

For a demonstration or additional information, call **+1.800.553.8033** or email **info@tennantco.com**